

Endress+Hauser Active barrier RN22-8L2BPA

Intrinsically safe active barrier that provides power and safety to analog instrument loops and SIL systems, establishing a reliable signal link between field devices and process control level.



Picture for reference only. Product appearance may vary based on configuration

The RN22 is a 1- or 2-channel active barrier, power supply or signal doubler for safe separation of 4 to 20 mA standard signal circuits. The device safely powers analog instrument loops and safety instrumented systems up to SIL 2, SC 3 (according to IEC 61508). The HART® transparent interface device establishes a reliable signal link between field devices and process control. It interfaces with 2- or 4-wire instruments in Zone 2 hazardous areas and provides a second, galvanically isolated signal output acc. to NAMUR NE 175. This opens a second channel for the process optimization domain without affecting the traditional automation system.

- Active barrier for safe separation of standard signal circuits
- Compact housing
- Quick and easy wiring
- Intrinsic safety for operation in hazardous areas (Zone 2)
- For safety-oriented applications up to SIL 2 (SC 3) in accordance with IEC61508 (optional)

Configuration of RN22-8L2BPA:

Approval:	8L	ATEX IECEx II(1)G [Ex ia Ga] IIC, II(1)D [Ex ia Da] IIIC, II3G Ex ec IIC Gc
Channel:	2	2-channel
Electrical Connection:	B	Push-in terminals
>>Accessory Enclosed:	PA	Power rail connector DIN rail 12.5mm

Alternative part number: RN22-12A5/0